Round Tapered Aluminum Pole with Arms Quad Bullhorn 180° — Breakaway T-Base 7'-6" 2'-6" 3'-9" Quad Bullhorn - 180° 2" NPS Schedule 40 Pipe Arms Aluminum Alloy 6063-T6 Stainless Steel Hardware Included **D** Top Diameter Mounting Height **B** Wall Thickness Tapered Aluminum Tube Alloy 6063-T6 **Finish** 01 = Satin Aluminum BA = Black Powder Coat BH = White Powder Coat BM = Dark Bronze Powder Coat BV = Dark Green Powder Coat GC = Gray Powder Coat ** = Specify Finish C Butt Diameter 4-Bolt Base Flange Aluminum Alloy 356-T6 With Aluminum Bolt Covers And Stainless Steel Hex Head Screws <u>-</u>5 Transformer Base FHWA Approved Breakaway WARNING: Do not install light pole without luminaire. Satin Aluminum or Powder Coated Finish per Customer Specification.

A Mtg. Hgt.	B Wall Thickness	C Butt Diameter	Lum. Weight	90	100	Maximum EP 110	A 120	130	Catalog Number
30	0.188"	10	25	5.2	3.8	3.4	2.4	1.6	RTA30D1CFB40-**

C Butt Dia.	D Top Dia.	F Bolt Cir. Dia.	G Base Sq.	H Bolt Proj.	 Bolt Size
10	6	15	15.375	3.5	1 x 48 x 4
					D: : : ! !

Dimensions in Inches

Customer Name:		
Project:	Location:	
Notes:		QUANTITY:

RTA30D1CFB40

CATALOG NUMBER

FINISH

Pole

The pole shaft will be constructed of seamless extruded tube of 6063 Aluminum Alloy per the requirements of ASTM B221. The shaft assembly shall be full-length heat treated after base weld to produce a T6 temper.

Base Style

Cast Aluminum Transformer Base (T-Base) of Alloy 356-T6 with Aluminum Door and Stainless Steel Hex Head Screw. FHWA Approved Breakaway.




Handhole

Tapered Door Opening (9-3/4" W Base x 9-1/4" W Top x 11-3/4" H) with Flush Mount Aluminum Cover and Stainless Steel Hex Head Screw. Grounding Provisions tapped 1/4"-20NC and 1/2"-13NC are provided.

Anchorage

Base Anchorage includes four
(4) L-shaped Steel Anchor Bolts
conforming to AASHTO M31490 Grade 55, four (4) each
Heavy-Duty Flat Washers, Lock
Washers, and Hex Nuts
(all components Galv. Steel).
Ten inches (10") of threaded
end will be galvanized per
ASTM A153. Top Connecting
Hardware includes four (4)
each 1"-8NC x 3-3/4" Hex Head
Bolts, Flat Washers, Lock Washers,
and Hex Nuts (all components
Galv. Steel). A bolt circle

template will be provided.



Vibration Damper

When determined necessary by Hapco, a Vibration Damper will be factory-installed inside the pole shaft. Customer specification of the damper is available.



EPA Notes: Effective Projected Area (EPA) in square feet. EPA's calculated using wind velocity (mph) indicated in accordance with 2009 AASHTO LTS-5 using a 25 year design life. Maximum EPA is based on the luminaire weight shown. Increased luminaire weight may reduce the maximum EPA. If weight is exceeded, or if other design life or code is required, please consult the factory.



26252 Hillman Highway Abingdon, VA 24210 800.368.7171 www.hapco.com