

A MTG. HGT.	B Wall Thickness	C Butt Diameter	J Arm Length	Lum. Weight	90	M <i>i</i> 100	хімим Е 110	PA 120	130	OLD Cat. Number	CATALOG NUMBER
40	0.219"	8	10'	35	7.9	4.9	4.1	2.4	1.1	43-334	RTA40E8BFD1A-**

C	D	F	G	H	
Butt Dia.	Top Dia.	Bolt Cir. Dia.	Base Sq.	Bolt Proj.	Bolt Size
8	4.5	15	15.375	3.5	

Dimensions in Inches

Customer Name:					
Рпојест:	Location:				
Notes:	(	QUANTITY:			

# RTA40E8BFD1A

CATALOG NUMBER

FINISH

#### Pole

The pole shaft will be constructed of seamless extruded tube of 6063 Aluminum Alloy per the requirements of ASTM B221. The shaft assembly shall be full-length heat treated after base weld to produce a T6 temper.

### **Base Style**

Cast Aluminum Transformer Base (T-Base) of Alloy 356-T6 with Aluminum Door and Stainless Steel Hex Head Screw. FHWA Approved Breakaway.




## **Handhole**

Tapered Door Opening (9-3/4" W Base x 9-1/4" W Top x 11-3/4" H) with Flush Mount Aluminum Cover and Stainless Steel Hex Head Screw. Grounding Provisions tapped 1/4"-20NC and 1/2"-13NC are provided.

# **Anchorage**

Base Anchorage includes four (4) L-shaped Steel Anchor Bolts conforming to AASHTO M314-90 Grade 55, four (4) each Heavy-Duty Flat Washers, Lock Washers, and Hex Nuts (all components Galv. Steel). Ten inches (10") of threaded end will be galvanized per ASTM A153. Top Connecting Hardware includes four (4) each 1"-BNC X-3-3/4" Hex Head Bolts, Flat Washers, Lock Washers, and Hex Nuts (all components Galv. Steel). A bolt circle

template will be provided.



## **Vibration Damper**

When determined necessary by Hapco, a Vibration Damper will be factory-installed inside the pole shaft. Customer specification of the damper is available.



EPA Notes: Effective Projected Area (EPA) in square feet. EPA's calculated using wind velocity (mph) indicated in accordance with 2009 AASHTO LTS-5 using a 25 year design life. Maximum EPA is based on the luminaire weight shown. Increased luminaire weight may reduce the maximum EPA. If weight is exceeded, or if other design life or code is required, please consult the factory.



26252 Hillman Highway Abingdon, VA 24210 800.368.7171 www.hapco.com