


# JEFFERSON 18

## CLAMSHELL - TAPERED FLUTED ALUMINUM POLE



Powder Coated Finish per Customer Specification.

C BUTT DIA.	D TOP DIA.	F BOLT CIR. DIA.	G BASE DIA.	H BOLT PROJ.	I BOLT SIZE
5	Varies	7.5 - 8	7.5	2	.75 x 17 x 3
6 (Up To .188")	Varies	9 - 10	9.75	2.75	.75 x 30 x 3
6 (.250" +)	Varies	9 - 10	9.75	2.75	1 x 36 x 4
7	Varies	10 - 11	10.5	2.75	1 x 36 x 4
8	Varies	11 - 12	11.25	2.75	1 x 36 x 4

Dimensions in Inches

### Clamshell Base


Cast Aluminum, 2-Piece Decorative Base of Alloy 356 per ASTM B26 or B108 with stainless steel attaching hardware.

### Pole

The pole shaft will be constructed of seamless extruded tube of 6063 Aluminum Alloy per the requirements of ASTM B221. The 4-Bolt Cast Aluminum Base Flange will be of Alloy 356-T6. The pole shaft shall be joined to the base by means of a complete circumferential weld in accordance with AWS Specification D1.2. The shaft assembly shall be full-length heat treated after base weld to produce a T6 temper.

### Anchorage

Anchorage Kit will include four (4) L-shaped Steel Anchor Bolts conforming to AASHTO M314-90 Grade 55. Ten inches (10") of threaded end will be galvanized per ASTM A153. Kits will contain four (4) Hex Nuts, four (4) Lock Washers, and four (4) Flat Washers (all components Galvanized Steel). A bolt circle template will be provided



**NOTE:** JEFFERSON 18 pole options may be specified in designs utilizing Direct Buried anchorage.

### Handhole

4"-5" Butt Diameters - 2" x 4" Handhole with curved Lap Style Aluminum Door and two (2) SS Self-Tapping Attaching Screws. A Grounding Provision incorporating a tapped 1/4"-20NC hole is provided.

6" Butt Diameter - Reinforced, 3" x 5" curved Cast Aluminum Frame (Alloy 356-T6) with Aluminum Door and two (2) SS Hex Head Screws. A Grounding Provision incorporating a 3/8" diameter hole is provided opposite the Handhole.

7"+ Butt Diameters - Reinforced, 4" x 6" curved Cast Aluminum Frame (Alloy 356-T6) with Aluminum Door and two (2) SS Hex Head Screws. Reinforced Frame will contain a tapped 3/8"-16NC Grounding Provision.

### Vibration Damper

When determined necessary by Hapco, a Vibration Damper will be factory-installed inside the pole shaft. Customer specification of the damper is available.



**WARNING:** Do not install light pole without luminaire.

www.hapco.com



1 OF 2

A MTG. HGT.	B WALL THICKNESS	C BUTT DIA.	TOTAL LUM. WEIGHT	MAXIMUM EPA						CATALOG NUMBER*
				90	100	110	120	130	140	
8	0.125	5	100	25.6	20.5	16.6	13.6	11.3	9.6	J8C08B5-4-TF**.**
10	0.125	5	100	19.4	15.3	12.3	10.0	8.2	6.8	J8C10B5-4-TF**.**
	0.188	5	100	29.4	23.4	19.0	15.6	13.0	10.9	J8C10D5-4-TF**.**
12	0.125	5	100	15.2	11.9	9.4	7.5	6.0	4.9	J8C12B5-4-TF**.**
	0.188	5	100	23.6	18.6	15.0	12.2	10.0	8.3	J8C12D5-4-TF**.**
	0.125	6	100	23.4	18.5	14.7	11.9	9.8	8.2	J8C12B6-4-TF**.**
	0.188	6	100	35.8	28.6	23.0	18.9	15.8	13.4	J8C12D6-4-TF**.**
14	0.125	5	100	12.1	9.3	7.2	5.6	4.4	3.5	J8C14B5-4-TF**.**
	0.188	5	100	19.2	15.0	12.0	9.6	7.8	6.4	J8C14D5-4-TF**.**
	0.125	6	100	19.0	14.8	11.6	9.3	7.5	6.1	J8C14B6-4-TF**.**
	0.188	6	100	29.6	23.4	18.7	15.3	12.6	10.5	J8C14D6-4-TF**.**
16	0.125	6	100	15.5	12.0	9.2	7.2	5.7	4.5	J8C16B6-4-TF**.**
	0.188	6	100	24.8	19.5	15.4	12.4	10.1	8.3	J8C16D6-4-TF**.**
18	0.125	6	100	12.4	9.4	7.0	5.3	4.1	3.1	J8C18B6-4-TF**.**
	0.188	6	100	20.4	15.9	12.4	9.8	7.9	6.4	J8C18D6-4-TF**.**
20	0.125	6	90	10.1	7.4	5.4	3.9	2.8	2.0	J8C20B6-4-TF**.**
	0.188	6	100	16.9	13.0	10.0	7.8	6.1	4.8	J8C20D6-4-TF**.**
	0.250	6	100	23.4	18.2	14.3	11.4	9.2	7.4	J8C20F6-4-TF**.**
	0.125	7	100	15.2	11.6	8.5	6.5	5.0	3.9	J8C20B7-4-TF**.**
	0.188	7	100	25.0	19.5	15.1	12.1	9.7	8.0	J8C20D7-4-TF**.**
	0.250	7	100	34.1	26.9	21.2	17.2	14.1	11.7	J8C20F7-4-TF**.**
	0.188	8	100	34.7	27.4	21.4	17.4	14.3	11.9	J8C20D8-4-TF**.**
	0.250	8	100	46.9	37.3	29.6	24.3	20.2	16.9	J8C20F8-4-TF**.**
25	0.312	8	100	58.6	46.8	37.4	30.8	25.7	21.7	J8C20G8-4-TF**.**
	0.188	8	100	23.5	18.2	13.6	10.7	8.5	6.8	J8C25D8-4-TF**.**
	0.250	8	100	32.8	25.7	19.8	15.9	12.9	10.6	J8C25F8-4-TF**.**
	0.312	8	100	41.6	32.8	25.7	20.9	17.1	14.2	J8C25G8-4-TF**.**

**EPA Notes:** Effective Projected Area (EPA) in square feet. EPA's calculated using wind velocity (mph) indicated in accordance with 2015 AASHTO LRFD (7th Edition) using a 50-year design life. Maximum EPA is based on the luminaire weight shown. Increased luminaire weight may reduce maximum EPA. If weight is exceeded, or if other design life or code is required, please consult the factory.

\*4-Bolt Base Anchorage shown. For direct buried design replace -4 in catalog number with -E.

**Catalog Number System**

The catalog number for Hapco poles utilizes the following identification system.



**Catalog Number Example -**

**J8C 20 F 6 - 4 - TF16 - BA**

JEFFERSON 18 Clamshell Base, 20' Mounting Height, .250" Wall Thickness, 6" Butt Diameter, 4-Bolt Base, Tapered Fluted Shaft - 16-Flute, Black Powder Coat Finish

**Wall Thickness**    **Butt Dia.**    **Anchorage**  
 B = .125"                      5 = 5"                      4 = 4-Bolt Base  
 D = .188"                      6 = 6"                      E = Direct Buried  
 F = .250"                      7 = 7"  
 G = .312"                      8 = 8"

**Shaft Style**  
 TF04 = Tapered Fluted – 4-Flute  
 TF08 = Tapered Fluted – 8-Flute  
 TF12 = Tapered Fluted – 12-Flute  
 TF16 = Tapered Fluted – 16-Flute

**Powder Coat Finish**  
 BA - Black Powder Coat                      BV - Dark Green Powder Coat  
 BH - White Powder Coat                      GC - Gray Powder Coat  
 BM - Dark Bronze Powder Coat              SC - Special Colors\*  
\* Provide RAL # or Sample Color Chip

**Mounting Options**

**Tenon Mount**  
 For Tenon Mount applications specify both Tenon diameter and length.



**Flute Options**



Tapered Fluted Mounting Heights				
Butt Diameter	TF-4 Up To	TF-8 Up To	TF-12 Up To	TF-16 Up To
5"	N/A	N/A	14'	14'
6"	N/A	N/A	20'	20'
7"	14'	14'	N/A	20'
8"	20'	20'	N/A	25'

**Direct Buried**  
 Direct Buried Mounting Heights may vary. Contact Hapco for maximum heights available.

CATALOG NUMBER:	QUANTITY:
CUSTOMER NAME:	
PROJECT:	LOCATION:
NOTES:	